






linear dimension(Tolerances Standard GB/T 14486-2008)								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
A	新发行		CLF	21.10.19

UL/CUL 技术参数					
UL/CUL Technical Data					
等级	Use Group	B	C	D	
额定电压	Rated Voltage	[V]	300	-	-
额定电流	Rated Current	[A]	2	-	-
接线范围	Wire Range	22/20-16			
单/多芯线	Solid/Stranded				[AWG]
耐电压	Withstanding Voltage	AC1600V/1Min			
IEC 技术参数					
IEC Technical Data					
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	
额定电压	Rated Voltage	[V]	250	320	630
额定电流	Rated Current	[A]	2	2	2
额定冲击电压	Impulse withstand voltagea	[kV]	4.0	4.0	4.0
导线截面积	Conductor cross section	0.5/1.5			
硬质/柔性导线	Solid/ flexible				[mm ²]
材 料					
绝缘材料	Insulation Material	热塑性材料/Thermoplastic			
导体材料	Contact Material	铜合金 Copper alloy			
导体表面镀层	Contactive Coating	镀锡 Tin Plated			
一般参数					
间距	Pitch	[mm]	3.5		
极数	Poles	[P]	01~XX		
剥线长度	Stripping Length	[mm]	8~9		
螺丝	Screw/扭矩	Torque(Max)	[N.m]		-
工作温度	Operating temperatur	[°C]	-40~+105		
引针尺寸	Pin Dimensions	[mm]	4.00		
PCB板孔径	PCB Hole Diameter	[mm]	1.30		
安装类型	Mounting type	波峰焊/Wave soldering			

DES.	SJD	DATE	21.10.19
CHK.	BY	DATE	21.10.19
APP.	CLF	DATE	21.10.19

单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1
慈溪市科发电子有限公司 CIXI KEFA ELECTRONIC CO., LTD					

第三视角/THIRD ANGLE PROJECTION	版本/REV	A
名称/TITLE	KF250-3.5C	